



Apseal™ Pro



**Premium open weave
fabric protector and water
repellent, quick drying formula**

Provides maximum water repellency,
stain protection, plus inhibits UV
damage and mildew growth.

Appearance and Odor: Clear, water white liquid with a mild solvent odor.

Coverage: Depending on the method of application and environmental conditions, you may expect approximately the following surface protection:

150 square feet per 32 oz. Spray; 600 square feet per gallon

Availability: 32 oz. Spray, Gallon, 5-Gallon Pail, 55-Gallon Drum

Applications: **Apseal Pro** may be used on most open weave fabrics to provide a protective stain and water repellent finish. For best results, **Apseal Pro** should be applied when fabric is dry.

Dilution and Use Directions:

1. Clean the fabric using **APCO FabClean Green**.
2. Apply **Apseal Pro** to clean, dry fabrics. Apply full strength from an appropriate hand pump sprayer in well ventilated area.
3. Spray **Apseal Pro** on the fabric in a slow sweeping motion 10-12 inches from surface. Cover thoroughly and completely but **DO NOT SATURATE**; 2 light coats will be more effective.
4. Let fabric dry thoroughly before use.

Important: Do not allow **Apseal Pro** to get on undesired surfaces, as it can be difficult to remove. Immediately clean up any over-spray.

Safety/Precautions: GHS Precautions: Keep container tightly closed. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Wear protective gloves/protective clothing/eye protection/face protection. Use explosion proof electrical/ventilating/lighting equipment. Take precautionary measures against static discharge. Keep only in original container. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapors/spray. Take off contaminated clothing and wash it before reuse. See SDS for other precautions and first aid. Protect from freezing. Rotate stock regularly. Keep out of reach of children. Best if used above 45°.

APCO Products are registered trademarks of APCO, LLC. 877-877- APCO (2726)